

DEALER / SALES REP: PRE-INSTALLATION CHECK LIST

Purchase Order Number:	Date:_				
This form must be completed in all sections, initial each Angelo PO America, you accept shipment of equipment	S S S S S S S S S S S S S S S S S S S	,	this form incomplete to		
End User:	Fnd User's Priman	End User's Primary Contact:			
Address:	End User's Primary Contact: End User's Contact Phone: Secondary Contact: Secondary Contact Phone:				
City: Zip Code:					
State2ip Code	Secondary Contact	riione.			
Project Company:	Project Company Main	Ph			
Project Manager:	Project Manager's Ph.	Project Manager's Ph			
1. Type of Premises:					
➤ Type of Facility: Hotel Hospital □ School /	University Production K	itchen □ Other □			
	-				
➤ New Construction* installation? Yes □ NO		itional charge must be	added to the PO)		
* New Construction that requires multiple trips to meet	contractor's requirements that are	e not included in the Cert	ified Install criteria can		
be added to the purchase order on Auto Quotes. If this	is not included on the purchase of	rder then any and all add	ditional cost will be the		
responsibility of the Dealer, end user and/or contractor					
2. Model of Oven:Add pl	hotos of oven installation location ar	nd location of the utilities	connection's.		
Oven will be Installed on to Angelo PO Stan	d ☐ On top of blast-chiller	□ Double Stacked			
Stacking ovens are only permitted on top of other Ar	ngelo Po products. Check approved	models.			
All gas shut-off valve must be installed within	n 3 feet of each oven prior to i	nstall?Phot	to Required		
Gas ovens are not to be used with any type	of GFCI or GFI outlet or circuit	t breaker.	<u></u>		
Electric ovens are not supplied with power c	ords, plugs, receptacle or con-	duit. End user must p	rovide before install.		
Are the door dimensions acceptable per atta		•			
	Toned dimension chart: 123 L	- NO -			
MODEL TYPE	WIDTH	DEPTH	HEIGHT		
FX61 FX101	36 7/32 36 7/32	30 9/16 30 9/16	24 13/16 34 1/2		
FX82	46 3/8	38	36 13/64		
FX122	46 3/8	38	47 3/64		
FX201	36 37/64	31 1/4	73 1/32		
FX202	46 39/64	38 11/32	72 39/64		
FX82 STACKED	48 19/64	46	72 13/64		
FX82 STACKED / CASTER CART	48 19/64	46	76 13/16		
Are the corridor dimensions acceptable for a	all ovens?				
The ceiling must have height clearance for s	stacking ovens (approx. 96 inc	hes)?			
Does the floor slope hinder the appliance to	be leveled correctly?	<u></u>			
Is the exhaust hood fully operational verify he	Is the exhaust hood fully operational verify hood is working by paper towel up against filter and stays in place?				
Oven clearance requirement is 6 inches from	n all sides?				
Water supply: Oven requires two ¾" connect	tions with shut off valves locat	ed within 36" of oven?	Photo Required		

1 | P a g e R e v . 11-23



DEALER / SALES REP: PRE-INSTALLATION CHECK LIST

>	Water Inlet pressure:	WITHOUT RO System=	30- 60psi			
		WITH Angelo Po RO=	50-125psi			
>	Distance from oven to w	ater connections (Inches)? _	Photo Required			
>	Drain connection located	within 5 feet of the oven?	Photo Required			
3. Spe	cial requirements for	models FX201-FX202				
>	Is there a 48 inches maneuvering space in front of the oven?Photo Required					
>	Are there floor grilles or discharge outlets in the cart maneuvering area?Photo Required					
4. Adja	acent appliances to th	e Oven				
>	Ovens Right Side:	Ovens Left	Side:Distance:			
5 Trav	/el & Mileage allowand	ο.				
J. IIa	_		ma and / as 100 miles' round trip from placest outhorized consis			
			me and / or 100 miles' round trip from closest authorized service			
	agency, the end user will be responsible for additional travel charges beyond the 2-hour /100 miles' allowance. This					
	will also apply to any wa	rranty service request during	g the warranty time period.			
6. Insta	allation:					
a.	a. Service agencies will require a minimum of 2-week advance notice for scheduling once a delivery date has been set.					
b.	o. Installation to be completed during normal business hours, (8:00am to 5:00pm M-F)					
C.	c. Should installation location exceed 2-hours travel time and / or 100 miles' round trip from closest authorized service					
	agency, the end user will be responsible for additional travel charges beyond the 2-hour /100 miles' allowance					
d. Gas ovens cannot to be used with any type of GFI outlet or circuit breaker.						
Comp	any Conducting Surve	ey:				
оор	y	, ,				
Dealer/	Rep / Service Co.:	nature Print Nam	me Date			
	•		, .			
Custor	ner:	Print Nam	me Date			
	-					
GBS V	P Service:					
	Signature	Print Nam	me Date			

2 | Page Rev. 11-23