

POMATI[®]
CHOCOLATE TECHNOLOGY

T 8



**Use and Maintenance
Instruction Manual**

We congratulate you on your great choice, and we thank you and invite you to read this manual to use this tempering machine with no risks and hazards.

While reading this manual you will have the opportunity to get the hang of your new machine, and appreciate all the production advantages. You will discover that this machine is very easy to use, and you will learn how you can easily change the process product, optimizing your own production by making it even more yielding; you will learn how applied technology can help you in your business. In fact, the machines manufactured by POMATI Group S.r.l. are the fruits of synthesis of years of experience in the designing and manufacturing of machines for processing chocolate.

The dedicated extreme scientific thoroughness and the high degreee of professional competence contribute towards enhancing its quality. Studies and close analyses, the use of modern technologies, choices of first-rate materials and components render this product by POMATI Group S.r.l. unique.

The quality mark characterizes all our machines, rendering them cost-effective, reliable, easy to use, requiring reduced maintenance, noiseless, safe and ergonomic.

In order to maintain POMATI Group S.r.l. machines perfectly in working order, it is imperative that the simple maintenance operations described herein be carried out.

Cleaning the machines is essential and necessary to maintain their reliability.

The onset of noises indicates the presence of anomalies. The operators who usually work with the machine can recognize their variations and detect their origin.

POMATI Group S.r.l. - in order to provide manuals even more thorough and comprehensive - asks for the precious collaboration of the users who can send their remarks or corrections stemming from their direct experience.

For the safety of operators, the integrity of machines, devices and systems, it is strictly forbidden to change the use or change any design parameter of the machine, device or system manufactured by POMATI Group S.r.l., to avoid warranty voidance and cancellation. Any changes shall be strictly forbidden and banned.

POMATI Group S.r.l. shall not be liable with the immediate cancellation of all warranties in case of change of use, cycle sequences, cycle time, speed, accelerations, in the event of replacement with non-original parts, improper use, tampering, mistreatment, lack of maintenance, removal of safety devices and, in general, of any changes made to the design parameters.

A highly-qualified service system is always at your disposal for any technical request and for assisting you while using the machine. Trying to solve the problem on your own, when you do not know the procedure, can pose hazards and may trigger further breakdowns and failures.

POMATI Group S.r.l. technical staff wishes you a continued success in using our machines!

This instruction manual belongs with the machine, therefore it must always be supplied with it, and in the event that the machine is sold, delivered to the new buyer.



TABLE OF CONTENTS

CHAPTER 1 INTRODUCTION

1.1 TESTING, WARRANTY AND LIABILITY	5/56-1
1.2 ENVIRONMENTAL CONDITIONS	5/56-1
1.3 INTERVENTION REQUEST - TECHNICAL ASSISTANCE	6/56-1
1.4 HOW TO ORDER SPARE PARTS	6/56-1
1.5 MARKING	6/56-1

CHAPTER 2 SAFETY RULES

2.1 GENERAL SAFETY NOTES	7/56-2
2.2 DEFINITION OF SAFETY TERMS	8/56-2
2.3 CORRECT USE OF THE MACHINE	8/56-2
2.4 TECHNICAL FEATURES OF THE MACHINE	8/56-2
2.5 OPERATOR'S POSITION	9/56-2
2.6 GENERAL DESCRIPTION AND DESCRIPTION OF MACHINE UNITS	10/56-2
2.7 SAFETY DEVICES	12/56-2
2.8 MACHINE ACCESSORIES	13/56-2
2.9 NOISE	13/56-2
2.10 VIBRATIONS	14/56-2
2.11 DEMOLITION AND DISPOSAL	15/56-2
2.12 EC DECLARATION OF MANUFACTURER - ROHS/RAEE	15/56-2

CHAPTER 3 HANDLING, INSTALLATION, ADJUSTMENTS

3.1 PACKAGE TRANSPORTATION	16/56-3
3.2 LIFTING	16/56-3
3.3 POWER SUPPLY	17/56-3
3.4 INSTALLATION AND COMMISSIONING	18/56-3

CHAPTER 4 USE OF CONTROLS

4.1 OPERATION CONTROLS	19/56-4
4.1.1 Electromechanical push-buttons placed on board	19/56-4
4.1.2 Functions of control panel	20/56-4
4.2 PROCESSING PHASES	22/56-4
4.2.1 Setting of tank heating temperature	22/56-4
4.2.2 Setting of Archimedean screw heating temperature	23/56-4
4.2.3 Setting of tempering temperature	24/56-4
4.2.4 Processing activity	25/56-4
4.2.5 End of processing stop	26/56-4
4.2.6 Machine discharge	27/56-4
4.2.7 Timing time adjustment	28/56-4
4.3 MENU OF MACHINE PROGRAMS	29/56-4
4.3.1 Set-up of general parameters	30/56-4
4.3.2 Clock	31/56-4
4.3.3 Password	32/56-4
4.3.4 Software info	32/56-4

CHAPTER 5 MAINTENANCE

5.1 MACHINE CLEANING	33/56-5
5.1.1 Machine cleaning from dark chocolate to milk chocolate to dark chocolate	33/56-5
5.1.2 Machine cleaning for passage from dark chocolate / milk to white chocolate / season end	34/56-5
5.2 MAINTENANCE	36/56-5
5.2.1 Replacement of fuses	36/56-5
5.2.2 Condenser cleaning	36/56-5

CHAPTER 6 DIAGNOSTICS

6.1 GENERAL WARNINGS	38/56-6
6.1.1 Alarm warning messages	38/56-6
6.1.2 Flowcharts	40/56-6

CHAPTER 7 SPARE PARTS AND WIRING DIAGRAM

7.1 SPARE PARTS	44/56-7
7.2 WIRING DIAGRAM	48/56-7



Pomati Group S.r.l.
Via A. Moro 14/16, industrial zone Mirandolina
www.pomati.it

Tel. (+39) 0377 33092
Fax. (+39) 0377 34446
pomati@pomati.it

DECLARATION OF CONFORMITY

(All. IIA DIR. 2006/42/CE)

THE MANUFACTURER

Pomati Group S.r.l.
Company
Via A. Moro 14/16, industrial zone Mirandolina
Address
Codogno
City

26845 LO
Zip code Province
Italia Country

DECLARES THAT THE MACHINERY

Tempering machine for chocolate
Description
000
Serial number
T8 Tempering machine for chocolate
Trade name
Machine designed and manufactured to melt and temper any type of chocolate
Intended use

2011 00 24/01/2010
Year of cast. Revision

COMPLIES WITH THE REQUIREMENTS

Directive 2006/42/CE of the European Parliament and the Council of 17 may 2006 on machinery, and amending directive 95/16/CE.

Directive 2004/108/CE of the European Parliament and the Council of 15 december 2004 concernente il riavvicinamento delle legislazioni degli Stati membri relative alla compatibilità elettromagnetica.

Directive 2006/95/CE of the European Parliament and the Council of 12 december 2006 concernente il riavvicinamento delle legislazioni degli Stati membri relative al materiale elettrico destinato ad essere adoperato entro taluni limiti di tensione.

Reference to technical standards harmonized:

UNI EN 894-2; UNI EN 1032; UNI EN ISO 13849-1; UNI ISO 2972; CEI EN 60439-2/Ec; UNI EN ISO 12100-2; UNI EN 1746; UNI EN 811; UNI EN ISO 13850; UNI EN 842; UNI EN ISO 5349-2; UNI EN 894-3; UNI EN ISO 13857; CEI EN 60439-1; UNI EN 1088; UNI 10893; CEI EN 60204-1; UNI EN 953; UNI EN 1037; UNI EN 981; UNI EN 983; UNI EN ISO 14121-1; UNI EN ISO 12100-1; CEI EN 60439-1/A1; UNI EN 415-1; CEI EN 60439-3; UNI EN ISO 11200; UNI EN 894-1; CEI EN 60439-2; UNI EN 349

AND HE AUTHORIZES

Gianni Lorenzani
Name
c/o G.L. Comunicazione s.r.l. - Via XXIV Maggio, 42
Address
Fidenza
City

43036 PR
Zip code Province
Italia Country

TO PREPARE THE TECHNICAL FILE FOR IT

Place and date of issue
14/11/2011

The manufacturer

D.C.: T8/000

Project: T8

project:

Machine:

T8

Tempering machine for chocolate

Year: 2011

G.L. Comunicazione s.r.l.

Mod.: T8

Serial number: 000

Rev.: 00 24/01/2010

Declaration CE of conformity



1.1 Testing, warranty and liability

Testing

The whole machine is sent to the customer and prepared to be installed after having passed all the tests and inspections laid down by the manufacturer in compliance with the regulations in force.

Warranty

During the twenty-four months of warranty, **Pomati Group S.r.l.** undertakes to provide those parts they manufacture which proved to be faulty due to materials or processing free of charge.

Such parts shall be returned to **Pomati Group S.r.l. carriage free**.

Warranty covers the supply of any faulty parts.

All the expenses of travelling, board and lodging, transport and labor regarding any replacement of the parts by Pomati Group S.r.l. engineers, which shall be entirely charged to the Buyer.

All those parts subject to wear shall not be covered by warranty.

As regards trade parts, the warranty set forth by the supplier shall be applied.

No compensation for expenses, damages or non-gain borne by the customer shall be acknowledged.

The installation of trade parts not complying with Pomati Group S.r.l. specifications - if trade - or not supplied by Pomati Group S.r.l. - if manufactured by them - cancels and voids the warranty as well as the machine misuse.

Liability

Pomati Group S.r.l. shall not be liable for anomalies in the machine operation or general breakdowns caused by the unauthorized use of the machine or by interventions and/or changes made by external people not authorized by **Pomati Group S.r.l.**

1.2 Environmental conditions

The machine working environmental conditions must follow the indications reported below:

Temperature 15°C ÷ +30°C (59°F ÷ 86°F)
Humidity 10% ÷ 90% (not condensed)



THE MACHINE MUST BE PLACED IN A PLACE SHELTERED FROM RAIN.

Environmental conditions differing from the ones specified herein may cause serious damages to the machine, in particular to the electrical equipment.



POSITIONING THE MACHINE IN PLACES DIFFERENT FROM THE ONES DESCRIBED HEREIN CANCELS AND VOIDS THE WARRANTY.

The storage of machine when not working allow temperature to range between +10°C (50°F) and +60°C (140°F), it being understood all the other precautions.



IT IS STRICTLY FORBIDDEN TO USE THE MACHINE IN PRESENCE OF EXPLOSIVE ATMOSPHERE OR FIRE HAZARD.

1.3 Intervention request - technical assistance

Every intervention request to the Customer Service must be submitted via fax or email to one of the following addresses:

Pomati Group S.r.l.

Customer Service

Telefax +39.0377.330.92
Email: pomati@pomati.it

specifying:

1. type of machine, serial number and year of installation;
2. defects noticed;
3. retailer where the machine was purchased;
4. fiscal document bearing witness to the date of purchase by the user.

1.4 How to order spare parts

Every request regarding spare parts must be submitted via fax or email to one of the following addresses:

Pomati Group S.r.l.

Customer Service

Telefax +39.0377.330.92
Email: pomati@pomati.it


specifying:

1. Machine model;
2. Serial number;
3. Code of the spare part to be ordered;
4. Required quantity;
5. Means of consignment.

1.5 Marking

All identification data of the machine are engraved on its rating plate. Such data shall have to appear always on every document exchanged between the user and the manufacturer, e.g. during every assistance request or when requesting spare parts, etc...

The ID plate is placed on the machines





2.1 General safety notes



THE RULES LISTED BELOW MUST BE CAREFULLY READ TO BECOME AN ESSENTIAL PART OF THE DAILY PRACTICE OF USING AND MAINTAINING THE MACHINERY, SO THAT ANY ACCIDENT TO PEOPLE AND/OR DAMAGES TO THINGS SHALL BE AVOIDED.

1. Do not try to start the machine until its functioning has been clearly understood.
2. Should any doubts arise, even after having carefully and thoroughly read this manual, turn to **Pomati Group S.r.l.** customer Service.
3. Make sure that the whole staff using the machine is informed of all the instructions regarding safety.
4. Before starting the machine, the operator shall check the presence of any visible defects on the safety devices and machine. In this case, immediately notify every apparent breakdown to Pomati Group S.r.l. or to the nearest Customer Service Center.
5. Daily check the correct operation of all the switches and safety devices.
6. Safety devices shall never be removed or made ineffective.
7. During the operations of maintenance, adjustment or repair it might be necessary to bypass some safety devices from the service. This operation must be carried out by authorized personnel only.
8. It is imperative that all the plates and signs placed on the machine be promptly replaced, should they be damaged.
9. The operator must know the function and position of the STOP and START buttons.
10. Replace the broken parts with original spare parts, guaranteed by the manufacturer.
11. Never try anything too risky!
12. All works on live parts shall be carried out by authorized personnel only, who shall work only with the machine unplugged.
13. Do not make any junctions in the electrical connections of electrical circuits.
14. Do not wear clothing, jewelry, accessories that may get caught in moving parts.
15. Keep the area surrounding the machine constantly free of any obstructions.
16. Always wear light gloves and caps and hair nets.
17. Pay the utmost attention to all the caution, warning and danger signs placed on the machine.
18. Enforce safety rules and make workers abide by them. Should any doubts arise, read this manual again before starting to work.
19. The machine shall be used solely for the purposes associated with its design and according to what was contractually laid down by **Pomati Group S.r.l.**



**DO NOT USE THE MACHINE FOR USES DIFFERENT FROM THE ONES DESCRIBED IN THIS MANUAL.
DO NOT PROCESS PRODUCTS DIFFERENT FROM THE ONES DESCRIBED IN THIS MANUAL.
DO NOT INCREASE THE MACHINE SPEED BEYOND THE VALUE INDICATED IN THIS MANUAL.**

The misuse of the machine may pose a hazard for the personnel working with it and damage the machine.

For any problem which might arise during the machine's service life and which was not included in this technical manual, please contact our Customer Service to solve the problem as soon as possible.

2.2 Definition of safety terms

The following terms shall be used throughout this manual referring to safety:

Dangerous zone	every zone inside and/or in the proximity of the machine where the presence of a person poses a risk for the safety and health of the personnel.
Exposed person	whoever finds themselves in a dangerous zone both completely and partially.
Operator	person in charge of installing, operate, adjust, service, clean, repair, transport parts of the machine and all the other activities required for its running.
Safety components	component specifically designed by the manufacturer and put on the market separately from the machine to perform safety functions. Safety component is that mechanism whose failure impairs the safety of exposed people.

2.3 Correct use of the machine

Tempering machine for confectionery, pastry making, ice-cream parlor and HORECA laboratories, designed and manufactured to melt and temper every type of chocolate. The direct tempering in Archimedean screw allows having a smooth chocolate and an optimal crystal cohesion at any time in order to make the final product a top-quality product.



THE MACHINE CANNOT BE USED FOR OTHER TYPES OF PRODUCTS WITHOUT POMATI GROUP S.R.L.'S AUTHORIZATION, WHICH SHALL NOT BE HELD RESPONSIBLE FOR THE DIRECT OR INDIRECT DAMAGES DERIVING FROM THE MACHINE MISUSE.


2.4 Technical features of the machine

1. Tank capacity: Kg 8
2. Heated chocolate tank with thermostat
3. Double heating circuit tank and Archimedean screw
4. Programmable switching on and off
5. Removable Archimedean screw for cleaning and changing chocolate
6. Archimedean screw backflow to discharge chocolate
7. High precision temperature control thermostats
8. Refrigeration unit with forced-air cooling system
9. Volt 200/400 – Hz 50/60 – KW 0,70 Trifase (Single phase upon request)
10. Dimensions: mm 360 (880 worktop included) x 450 x h 1040



2.5 Operator's position

T8 series requires a single operator who shall stand in front of the machine.



The operator can control the chocolate flow by means of the pedal placed in the bottom part of the machine.




2.6 General description and description of machine units

The Tempering machine T8 for chocolate was conceived for an easy and friendly use by the user, extremely functional for every kind of processing, suitable for the praline industry and for filling hollow parts or as support to confectionery decorations.

Thanks to the Archimedean screw - controlled by a refrigeration unit - the tempering process is carried out very quickly with excellent results. Crystal separation and the consequent rejoining is accomplished within the times required by the product, thus giving chocolate a great glossiness and sheen, and making it last in time.

T8 series consists of a series of units which interact so that their functionality is always effective. The identifiable units are the following:


1. **Processing pipe**
2. **Probe**
3. **Switch**
4. **Discharge pipe cap**
5. **Power cord**
6. **Draining grid**
- 6a. **Grid resistance**
7. **Worktop**
- 7a. **Vibrating table mat**
8. **Condenser**
9. **Refrigeration compressor**
10. **Product tank**
11. **Tank/Archimedean screw connection pipe**
12. **Stirrer**
13. **Controls panel**
14. **Safety microswitch**
15. **Stirrer motor**
16. **Pedal doser**
17. **Archimedean screw resistance**
18. **Tank resistance**
19. **Archimedean screw motor**
20. **Rear wheels**
21. **Emergency push-button**
22. **Processing pipe fixing ring nut**
23. **Archimedean screw**
24. **Vibrating table motor**
25. **Switches for worktop vibration and heating**
26. **Front wheels fitted with brake**
27. **Archimedean screw reduction gear**
28. **Tank heating probe**
29. **Tank reduction gear**
30. **Archimedean screw reduction gear**
31. **Scraper**



2.7 Safety devices

The T8 series tempering machine for chocolate is fitted with a safety device protecting the stirrer. When the worktop is removed, the microswitch is tripped, stopping the stirrer motor, and a red mushroom-head push button on a yellow background placed in the machine top part to protect both the operator and the machine. It shall be pressed in case of danger. Its enabling immediately halts the machine operation without removing the power supply from the main board and the operator's panel. To reset the operating conditions it is necessary to:

1. Remove the cause of the stop;
2. Lift the red mushroom-head push button to reset it;
3. Press the START push-button





2.8 Machine accessories

T5 tempering machine for chocolate comes with the following accessories:

1. Translated use and maintenance manual
2. Power cord
3. Tank cover

2.9 Noise


The machine is designed and engineered to minimise noise level at the source.

The measurements done at operator's location on a similar machine gave the following values:

The values found are the following:

1 level of acoustic pressure equivalent weighted **A**: $LA_{eq} = 1,2 \text{ dB(A)}$
 2 level of acoustic power emitted by the machine weighted **A**: $Lpc < 5 \text{ dB(C)}$

The measurement of the level of acoustic pressure equivalent weighted **A** results in conformity with the standard EN ISO 3744. As foreseen by this standard, the machine is positioned with its centre in correspondence to the centre of the reference fictitious parallelepiped, the longitudinal axis directed like the x axis and the back part turned towards the front point 1 (see following figure).



Observation:

Once the machine has been positioned, the time for the machine to warm up is awaited, until it reaches the normal working temperature.

The instrumentation used for measuring is the following:

- Integrating noise meter Brüel & Kjær mod. 2221 class 1 instrument in conformity with the standards IEC 651 and IEC 804
- Noise level gauger 4230 class 1in conformity with the standard IEC 942


If the machine is placed in a reverberating environment or where there are other sources of noise and the daily exposure is higher than 85 dB(A), these imply conditions of risk; therefore, in this case the employer is obliged to provide individual protection devices for the workers (earmuffs, plugs).

2.10 Vibrations

Determination of the vibration level generated by the equipment- $A_{(w)sum}$

The magnitude of the vibrating stresses generated by the equipment shall have to be characterized, for every exposure condition, in terms of "Equivalent Frequency-Weighted Acceleration" $A_{(w)} \text{m/s}^2$. The equivalent acceleration, which is preferably expressed (*) in S.I. units of measurement (meters per second squared - m/s^2), shall have to be quantified for every handle along three standardized directions **X**, **Y** and **Z**, by applying the weighted frequency provided for by the standard (W_h), which states the maximum hand-arm system sensitivity to vibratory stimuli with a frequency ranging between 5.6 and 1400 Hz.

Such an interval turns out to be delimited by the octave-band nominal frequencies 8 and 1000 Hz (included), or by the one-third octave bands with nominal frequency ranging between 6.3 Hz and 1250 Hz (included).



The three axial results shall have to be summed sectorally in order to obtain the total weighted acceleration:

$$A_{(w)sum} = \sqrt{a_{wx}^2 + a_{wy}^2 + a_{wz}^2}$$

The three standardized directions refer to a biodynamic system of coordinates, having their origin connected with the summit of the third metacarpal bone and the **Z** axis, determined by the longitudinal axis of this bone, the **X** axis crosses the palm of the hand while the **Y** axis is orthogonal to the two previous ones.

On the basis of the measurements, carried out through an operative simulation at the test room of the company **Pomati Group S.r.l.** by conforming to the UNI EN ISO 5349-1:2004.

THE TEST DOCUMENTS AND THE CERTIFICATES OF THE TOOLS ARE HELD BY THE COMPANY POMATI GROUP S.R.L. AND THEY ARE KEPT AT THE DISPOSAL OF THE RELEVANT CONTROL AUTHORITIES.




2.11 Demolition and disposal

The manufacturer expects an estimated service life of 45,000 hours of operation under normal conditions of use. At the end of the actual service life cycle, the company using the product shall dispose of the machine in compliance with the regulations in force, first of all emptying the lubricating fluids and cleaning the various parts, then separating the parts which form the machine.

It is necessary to differentiate the various materials pursuant to what is laid down by the regulations in force in the Country where the machine must be disposed of. The machine does not contain any hazardous components or substances requiring special procedures for their disposal.



DISPOSE OF THE PRODUCT ABIDING BY THE REGULATIONS IN FORCE IN EACH COUNTRY. STORE THE POLLUTING MATERIALS SUCH AS OILS AND SOLVENTS INSIDE METAL DRUMS ONLY.



2.12 EC Declaration of manufacturer - ROHS/RAEE

DIRECTIVE 2011/65/EU (Directive RoHS) of the European Parliament and of the council of 08 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

DIRECTIVE 2002/96/CE (Directive WEEE) of the European Parliament and of the council of 27 January, on waste electrical and electronic equipment. With reference to the above Directives and in particular to ENCLOSURES "I A" and "I B" of Directive 2002/96/CE, Pomati Group S.r.l., declares that its products.

DO NOT FALL WITHIN THE FIELD OF APPLICATION OF THE 2011/65/EU DIRECTIVE

Restricted substances referred to in Article 4(1) and maximum concentration values tolerated by weight in homogeneous materials:

Lead	(0,1 %)	Mercury	(0,1 %)
Cadmium	(0,01 %)	Hexavalent chromium	(0,1 %)
Polybrominated biphenyls (PBB)	(0,1 %)	Polybrominated diphenyl ethers (PBDE)	(0,1 %)

Raw materials used by Pomati Group S.r.l., in its components, fall within the EXEMPTIONS limits.

All surface treatments and plastic materials in Pomati Group S.r.l., products do not contain the prohibited substance listed in the 2002/95/CE directive.

EC DECLARATION OF MANUFACTURER - REACH


DIRECTIVE 2006/121/EC (REACH Directive) of the European Parliament and Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.

With reference to the above-mentioned Directives, **Pomati Group S.r.l.** declares that the products they market have been pre-registered by our suppliers on December 1st, 2008.

Pomati Group S.r.l. products do not originally contain any SVHCs (Substances of Very High Concern) in total percentage exceeding 0,1%.

3.1 Package transportation

Handle by means of transpallets by fitting the forks into the suitable seats of pallet. Use transpallets with an adequate capacity (<150 Kg). Upon delivering the machine, it is necessary to check that damages which could impair the correct machine operation - besides visible damages - were not caused.



3.2 Hoisting

Once the package has been brought near the place where the machine shall be installed, it is necessary to open the package by cutting the straps (A) and slipping off the carton (B); take the documents enclosed to the machine (C), remove all the covering parts used in the machine packaging, cut the straps tying the machine to the pallet (D).



TWO PEOPLE ARE REQUIRED TO HOIST THE MACHINE, AND SET IT BACK ON THE GROUND.



In the event that the machine is stored during extended periods of inactivity, it is recommended to store it indoor, sheltered against bad weather, in a chemical-free environment.

Before storing it, it is recommended to unplug it and thoroughly clean the machine. The machine must be stored in environments at appropriate temperature (from +10° C to + 60° C) / (from 50° F to 140°F).

3.3 Power supply

T8 tempering machine for chocolate must be powered with a voltage corresponding to the value indicated in the CE rating plate. Plug the machine only into a line with efficient earthing cable. In case of doubts, do not plug the machine.




USING TOO LONG EXTENSION CORDS OR CURRENT GENERATORS MAY CAUSE THE FOLLOWING PROBLEMS:




1. **SLOW MOTOR START WITH PROTECTION INTERVENTION;**
2. **MOTOR OVERHEATING WITH DECREASE IN POWER;**
3. **FAILURE OF ON-OFF SWITCH**

3.4 Installation and commissioning


Upon installing the tempering machine, and whenever the machine needs to be restarted after a period of inactivity, a first commissioning is required:



1. Fit the processing pipe into the suitable seat and screw the fixing ring nut (A).
2. Assemble the worktop onto the tank, making sure that the pin (B) is fully inserted into the hole (C).



3. Insert the plugs (D) and (E) into their respective connectors placed on the machine side; make sure that the power cord color matches the color of the sticker placed above the switches. The plug with the black power cord (E) shall be paired with the black sticker (E1) - start of the worktop vibration, - the plug with the grey power cord with the red heat-shrinkable sheath (D) shall be paired with the switch with the red sticker (D1) - start of the draining grid heating.



4. Insert the power cord plug into the suitable socket and enable the main switch (F) located at the rear of the machine.

A 2-hour pre-heating is recommended upon each start to optimize the machine operation




**POMATI GROUP SHALL NOT BE LIABLE FOR DAMAGES CAUSED TO THE PROCESSED CHOCOLATE AND FOR MISUSING THE TEMPERING MACHINE.
SHOULD ANY DOUBTS ARISE, REFER TO THIS MANUAL BEFORE ACTING.**



4.1 Operation controls

4.1.1 Electromechanical push-buttons placed on board

1. Archimedean screw rotation reversal	Key usually enabled at the end of the production. It allows discharging chocolate from the processing pipe into the heated tank. This function is also used to change chocolate. It can be used only when the stirrer motor is not working and the machine is in heating function. It is necessary to hold the button down to make the Archimedean screw rotation reversal work.
2. Emergency stop	Red mushroom-head push button on a yellow background. Placed to protect the operator and the machine, it shall be pressed in case of danger. Its enabling immediately halts the machine operation without shutting off the voltage from the main control board and operator's panel.
3. Pedal	Control pedal that allows the operator to insert the mould to be processed. This control is synchronized with the operator's panel. The times can be modified only by means of the operator's panel.
4. Heating	Fixed two-position luminous push-button. It enables or disables the worktop heating.
5. Vibration	Fixed two-position luminous push-button. It enables or disables the worktop vibration.



4.1.2 Functions of control panel



1. <i> MENU</i>	To enter the programming menu and start the process operating cycle by entering or modifying the preset parameters. Functional parameters can be changed only by highly skilled personnel, and are password protected.
2. <i> Down arrow key</i>	To scroll programming pages upward or, once inside the recipes, increase the parameters. These data are displayed on digital display.
3. <i> Up arrow key</i>	To scroll programming pages upward or, once inside the recipes, decrease the parameters. These data are displayed on digital display.
4. <i> ENTER</i>	Confirmation key. To enter and display parameters contained inside the programming pages or confirming data entry.
5. <i> Tempering key</i>	It can be enabled only in combination with the stirrer. It starts chocolate tempering cycle. Check the correct temperature through the display so that chocolate is brought to the desired crystallization - the one producing a chocolate that breaks but at the same time that softly melts. Its operation activation is signalled through a LED.
6. <i> Heating key</i>	Key usually enabled upon switching the machine on. It allows heating the tank to the temperature set by the operator and it is displayed on the screen. Its operation activation is signalled through a LED.



7. Stirrer	It enables or disables the function of motor and of stirrer inside the tank. Its functioning is not immediate, since it is enabled only when set heating temperature is reached. At the end of the 2-hour pre-heating set in the program, a safety device inhibits its operation if the worktop has not been correctly assembled.
8. Archimedean screw rotation/stop	Enables or disables the Archimedean screw motor operation; its operation is not immediate, since it is enabled only when the set heating temperature is reached, and at the end of the 2-hour preheating set by the program, a safety device inhibits its operation, if the worktop is not correctly assembled.
9. Doser	Programming push-button of the chocolate dosing time through the pressure of the pedal doser. After having set the dosing time, press and hold the pedal down to obtain the chocolate dosing; the flow will stop at the end of the set time for a time preset by the manufacturer in order to allow the mould to be placed under the processing pipe. Upon releasing the pedal the machine resumes its regular functions.
10. Digital display	To display the set data and information to use T8 tempering machine for chocolate, to extend LCD life span. If the push-button panel is not used for 10 minutes, it automatically turns off. It can be reactivated by simply pressing any key.



THE OPERATOR DIRECTLY ACTS ON THE TEMPERING MACHINE CENTRAL UNIT AND/OR PLC BY MEANS OF THE PUSH-BUTTON PANEL. FOR THIS REASON, EVERY OPERATION MUST BE CARRIED OUT BY PAYING THE UTMOST ATTENTION.

IF A SETTING GIVEN BY THE OPERATOR IS NOT CARRIED OUT BY THE MACHINE, MAKE SURE THAT THE MIXTURE PROCESSING CONDITIONS ALLOW THE ORDERED PROCESSING BEFORE DECLARING A HYPOTHETICAL FAILURE OR MALFUNCTIONING.



ANY CHANGES MADE WITHIN THE PROCESSING PARAMETERS WILL BE AUTOMATICALLY RECORDED, IF THEY ARE NOT CONFIRMED WITHIN 60 SECONDS BY PRESSING THE ENTER KEY.


4.2 Processing phases

4.2.1 Setting of tank heating temperature

Press the enter key to change chocolate melting temperature inside the tank.



The data (A) starts flashing on display.



It is possible to change the melting temperature by means of the up and down arrow keys; temperature inside the tank is increased using the up arrow key (B), while it is diminished using the down arrow key (C).



The new set data will be confirmed by pressing the "enter" key twice.







4.2.2 Setting of Archimedean screw heating temperature

Press key twice to change the heating temperature of chocolate Archimedean screw.



The data (A) starts flashing on display.

It is possible to change chocolate temperature inside the Archimedean screw by means of the up and down arrow keys; temperature inside the tank is increased using the up arrow key (B), while it is diminished using the down arrow key (C).



The new set data will be confirmed by pressing the "enter" key.




4.2.3 Setting of tempering temperature

Set the machine on cooling function by pressing the key (A); the key LED will turn on and




the snowflake will be displayed on screen.




Press the enter key twice to change the temperature in cooling function (tempering).



The data (B) starts flashing on display.




It is possible to change tempering temperature by means of the up (C) and down (D) arrow keys; temperature is increased using the up arrow key (C), while it is diminished using the down arrow key (D).



The new set data will be confirmed by pressing the "ENTER" key.



Reset the machine to heating mode by pressing the key (A); the LED will turn on displaying the activated mode.





4.2.4 Processing activity

Once the first commissioning operations have been successfully completed and the correct heating and tempering temperature have been set, the chocolate mass can be put inside the machine. If it is solid, wait for it to be completely melted.



BEFORE STARTING THE STIRRER, IT IS NECESSARY THAT THE MELTED CHOCOLATE MASS HAS REACHED THE CORRECT HEATING TEMPERATURE.



IF CHOCOLATE THAT HAS ALREADY REACHED THE PROPER TEMPERATURE IS INSERTED, AND THE MACHINE HAS BEEN JUST STARTED, IT IS POSSIBLE TO BYPASS PRE-HEATING BY CHANGING THE CONFIGURATION THROUGH GENERAL PARAMETERS.





START THE STIRRER BY PRESSING THE PUSH-BUTTON (A) AND THE ARCHIMEDEAN SCREW THROUGH THE PUSH-BUTTON (B). WAIT FOR THE CHOCOLATE TO COME OUT FROM THE PROCESSING PIPE.



SHOULD THIS NOT HAPPEN, STOP THE ARCHIMEDEAN SCREW BY PRESSING THE PUSH-BUTTON (B) AND CHECK THE HEATING TEMPERATURE OF THE PROCESSED CHOCOLATE.

UNDER IDEAL WORKING CONDITIONS, ALLOW THE CHOCOLATE TO FLOW FOR AT LEAST 10 MINUTES TO STABILIZE IT BEFORE STARTING THE TEMPERING PHASE.



Check chocolate heating temperature by enabling the probe found on the processing pipe. Press the key (C); the LED on the frost side will turn on, and the actual temperature of chocolate will be displayed. Displayed data (D).


If the output temperature detected by the probe equals or is close to the heating temperature, then chocolate can be tempered.

Otherwise the key (C) must be pressed; the LED on the flame side will turn on. Wait another 10/15 minutes before checking the actual temperature of chocolate again.


Once the chocolate has reached the correct heating temperature, it is prepared for the tempering cycle. Let the chocolate flow and wait for the temperature displayed on the screen to equal the one previously set. The machine takes approximately 15/20 minutes to reach the tempering temperature; once the preset temperature has been reached, wait a further 5 minutes for the mass to stabilize.

4.2.5 End of processing stop

Once the processing is over, bring the machine back to the heating cycle by pressing the key (A); the LED on the flame side will turn on.




wait 10 minutes and then stop the Archimedean screw by pressing the push-button (B).



THE MACHINE IS PROGRAMMED TO AUTOMATICALLY TURN THE MOTOR OFF AFTER A 10 MINUTE PRE-HEATING.



WHEN THE COOLING PHASE IS OVER, PRESS THE ARCHIMEDEAN SCREW STOP KEY (B): THE LED STARTS FLASHING AND “AUTOMATIC STOP OF THE ARCHIMEDEAN SCREW!” IS DISPLAYED. AT THE END OF THE PROGRAMMING MINUTES, THE ARCHIMEDEAN SCREW MOTOR AUTOMATICALLY STOPS.



THE PROGRAMMED SWITCH-OFFTIME IS DISABLED BY PRESSING THE ARCHIMEDEAN SCREW ENABLING KEY (B) TWICE. “MANUAL STOP OF THE ARCHIMEDEAN SCREW!” IS DISPLAYED ON THE SCREEN. THE OPERATOR HAS THE TASK OF DECIDING WHEN TO SWITCH OFF THE ARCHIMEDEAN SCREW MOTOR.



IN THE MANUAL FUNCTION, POMATI GROUP RECOMMENDS TO ALWAYS WAIT 10 MINUTES; BEFORE SWITCHING OFF THE ARCHIMEDEAN SCREW PRESS THE PUSH-BUTTON (C) TO STOP THE STIRRER MOTOR.



IT IS ADVISABLE TO KEEP MELTED CHOCOLATE AT THE PROPER TEMPERATURE. TO THAT END, DO NOT UNPLUG POWER SUPPLY DURING THE MACHINE STOP PERIOD.



4.2.6 Machine discharge




BEFORE DISCHARGING THE MACHINE, IT IS NECESSARY TO GET AN ADEQUATE CONTAINER TO COLLECT THE CHOCOLATE LEFT INSIDE.

Start the Archimedean screw (A) and collect the chocolate coming out from the processing pipe inside the container which was prepared in advance (B).




Stop the Archimedean screw when the tank is empty by pressing the push-button (A) and stop the stirrer by pressing the push-button (C); LEDs will go out.



Place a container (D) suitable for collecting the chocolate below the discharge pipe beside the tempering machine; remove the closing cap (E) from the discharge to collect the chocolate (F) which remained inside the processing pipe.

Start Archimedean screw rotation reversal by holding the button (G) down until all chocolate still found in the machine has come out.

Release the button and re-mount the cap of the discharge pipe.




**WHEN WORKING WITH WHITE CHOCOLATE, IT IS NECESSARY TO THOROUGHLY CLEAN SOME PARTS OF THE MACHINE.
REFER TO THE SHEETS CONTAINED IN THIS CHAPTER TO MAINTAIN AND CLEAN THOSE PARTS.**

4.2.7 dosing time adjustment

Set the machine on dosing cycle operation through the pedal doser. By pressing the push-button (A), the push-button led goes



on and the dosing parameter which was previously set is displayed.




In order to change the time inside the dosing operation, it is necessary to press the enter push-button;



the displayed data (B) starts flashing on the screen-page.


It is possible to change the dosing time by means of the up and down arrow keys. The up arrow key (C) increases the seconds, while the down arrow key (D) decreases the dosing seconds.



The new set data shall be confirmed by pressing the "ENTER" push-button.



During the regular operating cycle, the display continues to show the time set by the operator (E); the numerical reference (F) is a countdown of the dosing time in progress. At the end the chocolate discharge is stopped to allow the operator to change the processing mould.






4.3 Menu of machine programs

A programming menu is found inside the control panel, from which some functional parameters of the machine can be modified and customized. Proceed as follows:

Press button "MENU" to access the index of functional parameters.



Through buttons "UP ARROW" (A) and "DOWN ARROW" (B) position the cursor on the selected parameter to be modified and

press button "ENTER" to confirm.

Position the cursor on the selected parameter to be modified inside the parameter by means of the arrow keys ; press button "ENTER" to enter.

Change the parameter by means of the arrow keys and press button "ENTER" to confirm.

Press button "MENU" to quit the programming menu.

4.3.1 Set-up of general parameters

LCD contrast:

To adjust the brightness of the display to the laboratory lighting.

MENU	
1)	CFG GEN STAN
2)	CLOCK
3)	PASSWORD
4)	INFO SOFTW.

Reverse LCD:

To modify display color. When "OFF" the display is blue with white digits, when "ON" the display is white with blue digits.

CFG GEN STAN:	
1)	LCD CONTRAST: <input checked="" type="checkbox"/>
2)	REVERSE LCD: OFF
3)	LANGUAGE: ITA
4)	DEACT PREHEAT: OFF
5)	HEAT TANK: ON
6)	HEAT SCREW: ON

Language:

To select the language according to the country where the machine is used.

CFG GEN STAN:	
1)	LCD CONTRAST: <input checked="" type="checkbox"/>
2)	REVERSE LCD: OFF
3)	LANGUAGE: ITA
4)	DEACT PREHEAT: OFF
5)	HEAT TANK: ON
6)	HEAT SCREW: ON

Pre-heating disabling:

To enable or disable the 2-hour pre-heating program which is active upon every switching on of the machine. In the "OFF" mode pre-heating is enabled; in the "ON" mode pre-heating is disabled.

CFG GEN STAN:	
1)	LCD CONTRAST: <input checked="" type="checkbox"/>
2)	REVERSE LCD: OFF
3)	LANGUAGE: ITA
4)	DEACT PREHEAT: OFF
5)	HEAT TANK: ON
6)	HEAT SCREW: ON

Tank heating:

To enable or disable the tank heating function in automatic mode upon every switching on of the machine. In the "OFF" mode tank heating is disabled; in the "ON" mode tank heating is enabled.

CFG GEN STAN:	
1)	LCD CONTRAST: <input checked="" type="checkbox"/>
2)	REVERSE LCD: OFF
3)	LANGUAGE: ITA
4)	DEACT PREHEAT: OFF
5)	HEAT TANK: ON
6)	HEAT SCREW: ON

Archimedean screw heating:

To enable or disable the Archimedean screw heating function in automatic mode upon every switching on of the machine. In the "OFF" mode Archimedean screw heating is disabled; in the "ON" mode Archimedean screw heating is enabled.

CFG GEN STAN:	
1)	LCD CONTRAST: <input checked="" type="checkbox"/>
2)	REVERSE LCD: OFF
3)	LANGUAGE: ITA
4)	DEACT PREHEAT: OFF
5)	HEAT TANK: ON
6)	HEAT SCREW: ON



4.3.2 Clock

MENU	
1) CFG GEN STAN	
2) CLOCK	
3) PASSWORD	
4) INFO SOFTW.	

MENU TIME	
1) DATE/TIME	
2) WEEK PROGR	

MENU TIME	
DATE :	27/01/11
WEEK DAY :	GIO
H/MINUTES:	14:49

MENU TIME	
1)	
2) WEEK PROGR	

WEEK PROGR 1/2	
QUALIF:	OFF

WEEK PROGR 1/2		
QUALIF:	ON	
MO:	08:00	20:00
TU:	---	---
WE:	---	---
TH:	---	---

day of the week and time can be changed.

Time menu:

it is the submenu of the clock program. The WEEKLY PROGRAM can be accessed from here and the heating resistance switching on and off is set.

When "OFF" the program is disabled and resistances work 24/7 (*machine always ON*).

When "ON" the program is enabled and resistance switching on and off is adjusted according to our needs and to optimize energy efficiency. From left to right, the first column shows the days of the week; set the switching off time in the second column; set the switching on time in the third column.



IT IS ADVISABLE TO SET THE HEATING RESTART AT LEAST 3 HOURS BEFORE THE USE.

4.3.3 Password

MENU
1) CFG GEN STAN
2) CLOCK
3) PASSWORD
4) INFO SOFTW.

4.3.4 Software info

MENU
1) CFG GEN STAN
2) CLOCK
3) PASSWORD
4) INFO SOFTW.

SOFTW VERSION
NAME : TPcT5 V. 2.0
DATE : 18/01/11
Checksum: 0C5D

SW version:

To display important data on the software version installed on the machine.



5.1 Machine cleaning

5.1.1 Machine cleaning from dark chocolate to milk chocolate to dark chocolate



MAKE SURE THE MACHINE IS STILL HOT FOR THIS OPERATION.

After having performed the operations described in the paragraph "**Machine discharge for chocolate change-over**", it will be necessary to unplug the power supply sockets (A) connected to the worktop and remove the worktop (B).



Clean the product tank by disassembling the stirrer (C) by rotating it clockwise (D). Use a soft cloth to clean the inside of the tank and thoroughly wash the stirrer.



THOROUGHLY WASH WITH HOT WATER ONLY. WATER TEMPERATURE SHALL NOT EXCEED 60°C.



DO NOT USE ANY TYPE OF DETERGENTS, SINCE ANY RESIDUES MIGHT CONTAMINATE THE CHOCOLATE DRY THE MACHINE PARTS THOROUGHLY.

5.1.2 Machine cleaning for passage from dark chocolate / milk to white chocolate / season end




VISUALLY CHECK THAT THE SWITCHES OF HEATING AND WORKTOP VIBRATION ARE ON OFF POSITION, AND UNPLUG THE POWER SUPPLY SOCKETS.

MAKE SURE THAT THE MACHINE IS UNPLUGGED FROM THE MAINS, BUT STILL HOT.



Remove the worktop (A); remove the processing pipe by unscrewing the fixing ring nut (B).



Unscrew and extract the probe (C) from the suitable support and unscrew the hexagonal cylindrical head screws (D) locking the Archimedean screw cover;



remove the cover (E) and screw one of the fastening screws (F) on the top of the Archimedean screw (G)



to make its grip and extraction from its seat easier.



THOROUGHLY WASH WITH HOT WATER ONLY. WATER TEMPERATURE SHALL NOT EXCEED 60°C.

Reassemble the machine following the assembly instructions in reverse order.



DURING THE REASSEMBLY PROCEDURE, PAY ATTENTION THAT THE GASKET (H) IS IN GOOD SHAPE AND CORRECTLY POSITIONED IN ITS SEAT WHILE REPOSITIONING THE ARCHIMEDEAN SCREW COVER.



To clean the tank it is necessary to disassemble the stirrer (I) turning it clockwise. Use a soft cloth to clean the inner part of the tank and thoroughly rinse the stirrer.



DO NOT USE ANY TYPE OF DETERGENTS, SINCE ANY RESIDUES MIGHT CONTAMINATE THE CHOCOLATE DRY THE MACHINE PARTS THOROUGHLY.




ONCE THE MACHINE HAS BEEN CLEANED AND DRIED, IT IS ADVISABLE TO LET IT ON FOR 12 HOURS SET TO A 50°C TEMPERATURE WITH THE ARCHIMEDEAN SCREW DISASSEMBLED TO ALLOW ANY RESIDUAL HUMIDITY TO EVAPORATE.



DURING CLEANING PHASES IT IS STRICTLY FORBIDDEN TO USE SCREWDRIVERS OR SHARP TOOLS TO AVOID WARRANTY VOIDANCE.

5.2 Maintenance

5.2.1 Replacement of fuses



If the machine does not power on, it is necessary to check the fuse. In case it is broken, it is necessary to replace it with one of the same rating.

Switch the machine off by means of the suitable switch, unplug the power cord, remove the front panel (A), lift the fuse holder (B) and take out the broken fuse (C); replace it with a fuse having identical characteristics and close the fuse-holder. Rinstallare attraverso le viti il pannello frontale, ridare tensione alla macchina.

5.2.2 Condenser cleaning

It is necessary to keep the condenser clean for the machine to work properly. Moreover, no dusty product shall be placed in front of the intake grid. Scheduling two cleaning interventions is required during the season.

Follow the instructions below:



Remove the frontal panel (A) by unscrewing the suitable locking screws (B) to access the filter (C);



proceed with cleaning the filter by means of a brush (D) or an air gun (E).



6.1 General warnings

Most anomalies and problems that arise during the machine operation are promptly signalled by the machine automatically:

- warnings and signals are only messages given by the machine to the operator while it is still working;
- alarms cause the machine stop with a warning message of emergency stop that occurred through the operator's panel.

To restart the machine it is first necessary to remove the cause that triggered the emergency.

General operator: searches for operation anomalies, and, if he can do that, he also removes the causes of the anomaly to reset the proper operation of the machine.

The maintenance electrician/mechanic: intervenes later, in the event that the operator could not identify the cause of the problem or that restoring the correct operation of the machine entails the execution of very complex operations.


You will find below type of alarms which might be displayed:

- tables of warnings and alarms:** complete list of all warnings and alarms with possible causes and any troubleshooters.
- List of operation anomalies:** list reporting operation anomalies which arose at times – according to one's own experience. Likely causes and troubleshootings are reported for each operation anomaly.

6.1.1 Alarm warning messages

Warning message “Wait Pre-heating!”:

It notifies the operator that the preset 2-hour pre-heating which automatically starts at every machine restart is in progress.



Warning message “Automatic Stop of the Archimedean screw !”:

Start of the programmed automatic program lasting 10 minutes. Once this time has elapsed, the Archimedean screw operation will stop in automatic mode.




Warning message “Manual Stop of the Archimedean screw!”:

This is the automatic function by-pass; the stop time of the Archimedean screw is established by the operator.




Alarm "KO Work Area":

Alarm signal that notifies the operator that the safety pin installed on the worktop is not properly fitted. The worktop must be repositioned checking that the safety pin is correctly fitted.



Alarm "Emergency Push-button":

Alarm signalling that the emergency push-button has been pressed. In order to enable the regular operation of the machine, it is necessary to reset the mushroom-head push-button pushing upward.




Alarm "Heat Engine Screw MAXT":

Alarm signal that notifies the operator that the Archimedean screw probe detected a temperature exceeding the maximum allowable one to be set on the thermal regulator. It is advisable to contact the manufacturer or authorized retailer.



IN THE PRESENCE OF AMBIENT TEMPERATURES EXCEEDING 50°C SOME OPERATION ANOMALIES MIGHT APPEAR AS "TANK PROBE MAXT"




Alarm "Heat Engine Tank MAXT":

Alarm signal that notifies the operator that the tank probe detected a temperature exceeding the maximum allowable one to be set on the thermal regulator. It is advisable to contact the manufacturer or authorized retailer.




IN THE PRESENCE OF AMBIENT TEMPERATURES EXCEEDING 50°C SOME OPERATION ANOMALIES MIGHT APPEAR AS "TANK PROBE MAXT".




Alarm "Sint. Diff. Probe":

Alarm signalling the likely breakdown of the probe detecting chocolate temperature placed on the processing pipe or a wrong power connection. It is advisable to contact the manufacturer or authorized retailer.



Alarm "Sint. Tank Probe":


Alarm signalling the likely breakdown of the heating probe placed on the tank or a wrong power connection. It is advisable to contact the manufacturer or authorized retailer.





Alarm "Screw Probe":


Alarm signalling the likely breakdown of the heating probe placed on the Archimedean screw or a wrong power connection.
It is advisable to contact the manufacturer or authorized retailer.



DURING AN ALARM DISPLAY, THE OPERATOR CAN DISPLAY ONLY THE TEMPERATURE PAGE BY PRESSING ABY BUTTON. THE WARNING SYMBOL KEEPS FLASHING IN THE MIDDLE OF THE PAGE.


Alarm "Archimedean screw Motor Thermal Relay":

Alarm signalling that the motor controlling the Archimedean screw speed underwent excessive strain, thus triggering the thermal relay to prevent more serious damage. In order to reset the correct operation, it will be necessary to wait for it to cool down to automatically reset the motor thermal relay.



Alarm "Tank Motor Thermal Relay":


Alarm signalling that the motor controlling the stirrer speed inside the tank underwent excessive strain, thus triggering the thermal relay to prevent more serious damage. In order to reset the correct operation, it will be necessary to wait for it to cool down to automatically reset the motor thermal relay.



6.1.2 Flowcharts


The machine can signal an operation anomaly through a condition.

Those anomalies are not always caused by mechanical troubles or electrical faults; they might be caused by operation parameters not correctly set or by the use of unsuitable products.








THE MACHINE DOES NOT REACH THE CORRECT TEMPERATURE DURING HEATING



THE MACHINE TEMPERATURE DOES NOT FALL DURING THE COOLING PHASE











7.1 Spare parts


Pos.	Code	Description	Quantity
1	019046	Processing pipe	no. 1
2	004011	Chocolate probe	no. 1
3	012032	Discharge cap	no. 1
4	004185	Grid resistance	no. 1
5	000036	Stirrer	no. 1
6	005037	Stirrer motor	no. 1
7	004052	Pedal doser	no. 1
8	004039	Archimedean screw resistance	no. 1
9	004040	Tank resistance	no. 1
10	005036	Archimedean screw motor	no. 1
11	002140	Rear wheels	no. 2
12	019011	Processing pipe fixing ring nut	no. 1
13	000205	Archimedean screw	no. 1
14	005006	Vibrating table motor	no. 1
15	002141	Brake front wheels	no. 2
16	014070	Tank cover	no. 1
17	009028	Serial number label	no. 1
18	009027	Electrical safety sticker	no. 1
19	014008	Stirrer baffle	no. 1
20	002035	O-ring	no. 1
21	002020	Vibrating table spring	no. 4
22	004180	Control board	no. 1
23	002059	Scraper	no. 1
24	014120	Vibrating table mat	no. 2
25	004019	Tank heating probe	no. 1
26	004019	Archimedean screw heating probe	no. 1
27	005042	Archimedean screw reduction gear	no. 1
28	005043	Tank reduction gear	no. 1
29	012004	Table microswitch pin	no. 1






Pos.	Code	Description	Quantity
1	019046	Processing pipe	no. 1
2	004011	Chocolate probe	no. 1
3	012032	Discharge cap	no. 1
4	004185	Grid resistance	no. 1
5	000036	Stirrer	no. 1
6	005037	Stirrer motor	no. 1
7	004052	Pedal doser	no. 1
8	004039	Archimedean screw resistance	no. 1
9	004040	Tank resistance	no. 1
10	005036	Archimedean screw motor	no. 1
11	002140	Rear wheels	no. 2
12	019011	Processing pipe fixing ring nut	no. 1
13	000205	Archimedean screw	no. 1
14	005006	Vibrating table motor	no. 1
15	002141	Brake front wheels	no. 2
16	014070	Tank cover	no. 1
17	009028	Serial number label	n. 1
18	009027	Electrical safety sticker	no. 1
19	014008	Stirrer baffle	no. 1
20	002035	O-ring	no. 1
21	002020	Vibrating table spring	n.o 4
22	004180	Control board	no. 1
23	002059	Scraper	no. 1
24	014120	Vibrating table mat	no. 2
25	004019	Tank heating probe	no. 1
26	004019	Archimedean screw heating probe	no. 1
27	005042	Archimedean screw reduction gear	no. 1
28	005043	Tank reduction gear	no. 1
29	012004	Table microswitch pin	no. 1



7.2 Wiring diagram












Note

Note



POMATI®
CHOCOLATE TECHNOLOGY

Pomati Group S.r.l.
via Aldo Moro 14/16
Z.I. Mirandolina - 26845 Codogno (LO)

AFFRANCARE




POMATI®
CHOCOLATE TECHNOLOGY

T 8

Warranty Certificate



B WARRANTY



Model

T8

Registration number

Purchaser

Address

Postal code

Town

Province

Phone

Telefax

Activity

Ice-cream

Horeca

Pastry making

Other

Date of purchase

□ □ □ 2 □ □

Name, address and stamp of the retailer

Data have been entered in our lists with a view to sending information and promotional material.

At any time, in line with art.13 of the law 675/96, you will be able to access your data, request modification or erasure thereof, or oppose their use by writing to:

Pomati Group S.r.l.

Via Aldo Moro 14/16 - Z.I. Mirandolina - 26845 Codogno (LO)

TO BE SENT ENTIRELY FILLED IN, WITHIN 10 DAYS FROM THE DATE OF PURCHASE.



A WARRANTY

TO BE SHOWN TO THE TECHNICIAN

Model

T8

Registration number

Purchaser

Address

Postal code

Town

Province

Date of purchase □ □ □ 2 □ □

Warranty clauses:

1. The machine warranty covers a 24-month period since the date of purchase.
2. The purchase date is the one indicated on the receipt for item purchased or invoice issued upon delivery of the machine by the retailer.
3. Any warranty becomes null and void if the B part is not entirely filled in and if sent later than 10 days after the date of purchase (postmark date).
4. By warranty we mean replacement or repair free of charge of components found to be defective since manufacturing.
5. Replacement of components, if made by the retailer, will be recognized free of charge once replaced components have been returned to our headquarters to be examined and declared as defective. Labor expenses are not included in the warranty.
6. All transport expenses will be charged on the purchaser.
7. The warranty does not cover parts subjected to wear, damage caused by negligence, improper use and installation and, in any case, issues not resulting from ordinary operation of the machine.
8. The warranty becomes null and void if the machine is tampered with or repaired by unauthorized personnel.
9. The warranty does not cover replacement of the machine and extension of the warranty following intervention for failure issues.
10. Nobody is entitled to modify the warranty conditions, nor to issue other warranties, in written or oral form, without the written authorization of Pomati Group S.r.l.
11. The warranty does not cover compensation for damage, either direct or indirect, of any nature, to persons or objects, resulting from use or suspension of use of the machine.

Date of production

□ □ / □ □ / □ □

Registration number

□ □ □ □ □ □ □

ED. 02/2013 - S. 01