



Food Service Gas Connector (EF-FSGC-Series)

SPECIFICATIONS

ID	Model #	Fittings	Lengths
1/2"	EFGC-012-BJ-1010	1/2" MIP x 1/2" MIP	24", 36", 48", 60", 72"
3/4"	EFGC-034-BJ-1414	3/4" MIP x 3/4" MIP	
1"	EFGC-010-BJ-1616	1" MIP x 1" MIP	

Tubing and Braid Material	Stainless Steel 304 (ASTM A240)
Coating	Yellow PVC, coating will not hold a flame
Fittings	Zinc-Plated Steel S45C
Max. Operating Pressure	1/2 psi

DESIGN CERTIFICATIONS AND APPROVALS

- ANSI Z 21.69/ CSA 6.16 Connectors for Movable Gas Appliances
- A Restraining device is required for all moveable gas equipment.



Connector Minimum Flow Capacity

Straight Length Capacity (BTU/Hr., 0.64 Sp Gr., 1,000 BTU per cubic ft. at 0.5 inch W.C. pressure drop)

Series	ID (OD)	12"	18"	24"	30"	36"	48"	60"	72"
012	1/2" (5/8")	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000
034	3/4" (1")	-	-	290,900	270,500	255,900	215,900	197,400	173,900
010	1"(1/4")			581,800	545,200	515,900	442,700	398,900	347,300

The above flow capacities are the minimum performance requirement. EASYFLEX Gas Connectors exceed these minimum flow capacities requirements.

Job Name :

Engineer / Architect :

Job Location :

Wholesaler :

Submittal Date :

Contractor :



WEST OFFICE
(888) 577-8999
EAST OFFICE
(855) 388-2600

Easyflex reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modification on Easyflex products previously or subsequently sold.