



REMOTE REFRIGERATION DATA

Refer to the chart below to determine the following remote characteristics: Voltage, Amps, BTU's and Refrigerant. The chart also indicates what components are included: Solenoid, Expansion Valve, and Temperature Control type.

MODEL NO	VOLTAGE	AMPS	BTU @ 90°F AMBIENT AND EVAP. TEMP.	REFRIG'T	SOLENOID YES/NO	EXP. VALVE YES/NO	TEMPERATURE CONTROL
R/A SERIES							
RHT132W	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT232W	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT332W	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT132N	115/60/1	5.4	2240 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT232N	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT332N	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT126W	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT226W	115/60/1	6	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT132D	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT232D	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT132WP	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT232WP	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT332WP	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RLT132N	115/60/1	5.4	1930 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RHT232NP	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT332NP	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT126WP	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RHT226WP	115/60/1	6	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RLT132W	115/60/1	5.4	2160 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT232W	115/60/1	8.5	3790 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT332W	115/60/1	8.5	5220 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT132N	115/60/1	5.4	1930 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT232N	115/60/1	8.5	3790 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT332N	115/60/1	8.5	5220 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT126W	115/60/1	5.4	1980 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT226W	115/60/1	6	3790 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT132D	115/60/1	5.4	2160 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RLT232D	115/60/1	8.5	3790 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RRI132L	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI232L	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI332L	115/60/1	8.5	5330 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI132LP	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI232LP	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI332LP	115/60/1	8.5	5330 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI132H	115/60/1	5.4	2400 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI232H	115/60/1	8.5	4360 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RRI332H	115/60/1	8.5	5330 @ +20°F Evap	R-407A	Yes	Yes	Smart Control
RIF132L	115/60/1	5.4	2160 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RIF232L	115/60/1	8.5	5220 @ -20°F Evap	R-407A	Yes	Yes	Smart Control
RIF332L	115/60/1	5.4	7580 @ -20°F Evap	R-407A	Yes	Yes	Smart Control



REMOTE REFRIGERATION DATA

NOTES:

1. Remote microprocessor and smart control equipped units do not require use of a temperature control.
2. Cord and plug are not supplied with remote units.
3. Listed BTU rating shown is the required BTU's delivered to the unit at the evaporator coil.
4. Compressor HP not supplied by Traulsen. Compressor size should be determined by a qualified refrigeration technician based on the delivered BTU rating at the unit and actual jobsite requirements.
5. To determine approximate remote model weights, please deduct 40 lbs. from the respective self-contained models net or gross weight.
6. Standard Traulsen seven year compressor warranty does not apply to remote units.
7. Condensate Removal: All remote models require provisions to be made to allow for condensate removal by the operator. As supplied standard, these models include only a drain tube exiting evaporator compartment on top of the cabinet from which condensate will drip. Optional condensate removal provisions include a drain line extended down the cabinet back (n/a for pass-thru or roll-thru models) or Top-Mounted Condensate Evaporator, all supplied by others.
Note: Provision of the first option will add approximately 7/8" to the overall cabinet depth.
8. Traulsen does not recommend the use of casters with remote models.
9. Refrigeration connections provided are 1/4" O.D. for the liquid line and either 1/2" or 3/4" O.D. for the suction line, no other connections are required.
10. The solenoid valve provided is wired at the factory directly to the control, therefore no electrical connections are required between the unit and remote compressor.
11. For optional refrigerant options consult with factory at time of order to ensure correct expansion valve is provided.