



**QUOTE DRAWING**

Sign below for acceptance

X \_\_\_\_\_

Door hinge: Left \_\_\_ Right \_\_\_

Door location wall (centered): Left \_\_\_ Front \_\_\_

By signing here, you agree to our terms and conditions as outlined on www.uscooler.com/terms. Panel configuration subject to U.S. Cooler final approval. A facsimile or emailed approval of this drawing F1810FL.PA95 shall have the same force and effect as a signed original and shall, upon receipt by U.S. Cooler, be binding on both parties.

**Materials:**  
 ExtMetal: Galvalume  
 IntMetal: Galvalume  
 Foam: Extruded 4in.

**Legend**  
 Ceiling - - - - -  
 Floor - - - - -

Freezer: 9'-9 1/2" x 7'-10" x 7'-6"

Scale: 3/8" = 1'



**FASTCOOLER**

by U.S. Cooler

401 DELAWARE ST. \* QUINCY, IL 62301

TEL 217-228-2421 \* 800-521-2665 \* FAX 217-228-2424

CUSTOMER \_\_\_\_\_

JOB# \_\_\_\_\_ P.O.# \_\_\_\_\_

DATE **07/10/2020** DRAWN **C.G. 1.0**

DWG. REF **F1810FL.PA95** APV. \_\_\_\_\_

To aid in packing, please indicate with an X the corner where installation will be starting.

Refrigeration Specifications								
Qty	Manufacturer	Model	HP	Electrical	MCA	CmpRLA	CmpLRA	Dimensions DxWxH
<b>Pre-assembled Remote Low Temp R404A Air Cooled Outdoor Condensing Unit</b>								
1	Tecumseh	ASHR2480ZNAMS	2.5	208-230/1Phase/60Hz		12.6	73.1	38.1"x39.9"x21.5"
1	Russell	RL6E066DEAA		208-230/1Phase/60Hz	10.8			15.5"x43.625"x18.125"