

# Product Specifications

Product Name	Norimaki Cutter for Commercial Use
Machine Name	MAKI CUTTER
Model Name	ASM260A
Power Source	AC110V - 120V, 50 / 60 Hz
Power Consumption	35 W
External Dimensions	<p>Approx. W 14.9 in. × D 11.4 in. × H 19.2 in. (max. 19.6 in.)</p> <p>Approx. W 379 mm × D 290 mm × H 487 mm (max. 497 mm)</p> <p>* Excluding the <b>Power Cord</b> and protruding parts</p>
Weight	Approx. 37.4 lbs. (17 kg.)
Processing capacity	<p>Max. 600 rolls/hour</p> <p>* Including Norimaki setting time of 2 seconds per roll</p> <p>small (0.94 in. (24 mm)) 4 rolls (2400 rolls/hour)</p> <p>medium (1.37 in. (35 mm)) 2 rolls (1200 rolls/hour)</p> <p>large (1.77 in. (45 mm)) 1 roll (600 rolls/hour)</p> <p>* The cutting capacity varies depending on the size of the Norimaki.</p>
Range of Norimaki sizes	<p>Thickness: equivalent to 0.94 in. (24 mm) square to 1.96 in (50 mm) square</p> <p>Length: lengthwise roll (for 6/8 pieces): 7.08 in. (180 mm) to 7.48 in. (190 mm)</p> <p>crosswise roll (for 10 pieces): 7.87 in. (200 mm) to 8.26 in. (210 mm)</p>
Cutting size	<p>For 6-piece cut: 1.18 in. (30 mm) each</p> <p>For 8-piece cut: 0.88 in. (22.5 mm) each</p> <p>For 10-piece cut: 0.78 in. (20 mm) each</p>
Fuse Capacity	2 amperes (A)
Power Cord	Grounding type Plug (9.8 ft. (3m) Cord) Inlet plug-in type